

### RUBBER HOSES – INDUSTRIAL & HYDRAULIC




**AIR DRILL BLACK HOSE**  
 Range : 20 mm to 75 mm ID  
**W.P. 34.5 kg/cm<sup>2</sup>**  
 Temp. -30°C to +82°C  
 Black / Yellow cover  
 (Flame Retardant - Yellow Colour)



**ROCK DRILL HOSE**  
 Range : 6 mm to 50 mm ID  
**W.P. 14 / 18 / 21kg/cm<sup>2</sup>**  
 Temp. -30°C to +82°C  
**I.S. 446 Type -III**




**HEAVY ROCK DRILL HOSE**  
 Range : 20 mm to 100 mm ID  
**W.P. 16 & 25 kg/cm<sup>2</sup>**  
 Temp. -30°C to +82°C  
**I.S. 446 : 1987 Type -III**



**ROCK DRILL HOSE WIRE BRAIDED**  
 Range : 20 mm to 75 mm ID  
**W.P. 40 to 60 kg/cm<sup>2</sup>**  
**B.P. 150 to 240 kg/cm<sup>2</sup>**  
 Temp. -30°C to +82°C




**AIR AND WATER HOSE**  
 Range : 12.5 mm to 100 mm ID  
**W.P. 12 kg/cm<sup>2</sup>**  
 Temp. -30°C to +82°C  
**I.S. 446 Type - I / I.S. 444 Type - II**




**PNEUMATIC TOOL HOSE**  
 Range : 6.3 mm to 50 mm ID  
**W.P. 14 kg/cm<sup>2</sup>**  
 Temp. -30°C to +82°C  
**I.S. 446 : 1980 Type II**




**FDA-GRADE CHEMICAL HOSE UHMWPE**  
 Range : 19 mm to 102 mm ID  
**W.P. 16 kg/cm<sup>2</sup>**  
 Temp. -25°C to 100°C  
 Steam Cleaning upto +130°C ( for Max 30 Minutes)



**XLPE CHEMICAL HOSE SOLVENT HANDLING HOSE**  
 Range : 25 mm to 50 mm ID  
**W.P. 14 kg/cm<sup>2</sup>**  
 Temp. -30°C to 90°C  
 Steam Cleaning upto +130°C ( for Max 30 Minutes)



**SAND BLAST HOSE SHOT BLAST HOSE**  
 Range : 20 mm to 75 mm ID  
**W.P. 7 / 10 / 12 kg/cm<sup>2</sup>**  
 Temp. -40°C to +70°C  
**IS 5894 : 1980 Type I and Type II**



**CEMENT GROUTING HOSE CONCRETE TRANSFER HOSE**  
 Range : 25 mm to 100 mm ID  
**W.P. 10 & 85 kg/cm<sup>2</sup>**  
**B.P. 30 & 255 kg/cm<sup>2</sup>**  
 Temp. -40°C to +70°C  
**IS 5137 : 1990**



### CARBON FREE HOSE

**NON - Conductive Hose**  
Range :12.7 mm to 76.2 mm  
W.P. 14 to 17 kg/cm<sup>2</sup>  
B.P. 56 to 69 kg/cm<sup>2</sup>  
Temp.-40°C to +100°C



### LONGWALL MINE HOSE

**Two Steel Braided  
MSHA**  
Range : 63.5 mm & 76.2 mm  
W.P. 69 kg/cm<sup>2</sup>  
B.P. 276 kg/cm<sup>2</sup>  
Temp. -40°C to +100°C



### SLURRY SUCTION HOSE

Range :31 mm to 150 mm  
W.P. 10 kg/cm<sup>2</sup>  
Temp. -40°C to + 70°C



### WATER SUCTION & DISCHARGE HOSE

Range :6.3 mm to 50 mm  
W.P. 7 & 10 kg/cm<sup>2</sup>  
Temp. -25°C to +70°C  
IS 3549 : 1983 Type I & Type II




### STEAM HOSE

Range :12.7 mm to 50 mm  
W.P. 7 kg/cm<sup>2</sup>  
Temp. - 165°C  
IS : 5122: 1975 Type II



### STEAM HOSE SINGLE WIRE

Range :20 mm to 50 mm  
W.P. 10 kg/cm<sup>2</sup>  
B.P. 100 kg/cm<sup>2</sup>  
Temp: - 40°C to +195°C  
IS: 10655 Type 2 & B.S. : 5342 Type 1



### SUPER STEAM HOSE DOUBLE WIRE BRAIDED

Range :12.7 mm to 50 mm  
W.P. 17 kg/cm<sup>2</sup>  
B.P. 170 kg/cm<sup>2</sup>  
Temp. -40°C to +232°C  
IS : 10655 Type 3 & B.S. : 5342 Type 2



### EPDM - FDA STEAM HOSE

**FOOD GRADE**  
Range :19 mm & 25 mm  
W.P. 6 kg/cm<sup>2</sup>  
Temp. -40°C to +164°C



### HOT WATER HOSE

Range :12.5 mm to 75 mm  
W.P. 7 kg/cm<sup>2</sup>  
B.P. 21 kg/cm<sup>2</sup>  
Temp. -30°C to + 100°C  
IS 5821/79



### STATIC CONDUCTIVE HOSE

Range:6.3 mm to 50 mm  
W.P. 30 to 37 kg/cm<sup>2</sup>  
B.P. 90 to 110 kg/cm<sup>2</sup>  
Temp. -40°C to +100°C



### BREWERY HOSE FOOD GRADE

Range: 22 mm to 100 mm  
W.P. 10 kg/cm<sup>2</sup>  
B.P. 30 kg/cm<sup>2</sup>  
Temp. -40°C to +100°C



### FDA - PHTHALATE FREE HOSE MILK, DAIRY PRODUCTS & FATTY FOOD

Range: 25 mm to 102 mm  
W.P. 10 kg/cm<sup>2</sup>  
B.P. 30 kg/cm<sup>2</sup>  
Temp. -20°C to +90°C  
Steam Cleaning upto +130°C ( for Max 30 Minutes)



### EPDM CHEMICAL HOSE

Range :19 mm to 50 mm  
W.P. 12 kg/cm<sup>2</sup>  
B.P. 48 kg/cm<sup>2</sup>  
Temp. -30°C to +100°C



**COMPOSITE HOSE**  
CHEMICAL / OIL / FUEL /  
AVIATION FUEL / TANKER /  
DOCK - HOSES  
Range :25 mm to 250 mm  
W.P. 7 to 14 bar  
Temp. -30°C to +80°C



**HYDRAULIC HOSES**  
**SAE R1 AT**  
Range :6.3 mm to 50.8 mm  
W.P. 40 to 230 kg/cm<sup>2</sup>  
B.P. 163 to 920 kg/cm<sup>2</sup>  
Temp. -40°C to +100°C



**HYDRAULIC HOSES**  
**SAE R2 AT**  
Range :6.3 mm to 50.8 mm  
W.P. 82 to 400 kg/cm<sup>2</sup>  
B.P. 325 to 1630 kg/cm<sup>2</sup>  
Temp. -40°C to +100°C



**THERMOPLASTIC RUBBER HOSE**  
**AIR / PNEUMATIC**  
Range :6 mm to 50 mm  
W.P. 14 to 22 kg/cm<sup>2</sup>



**THERMOPLASTIC RUBBER HOSE**  
**WATER - HOSE**  
Range :12.5 / 20 / 25 mm  
W.P. 10 kg/cm<sup>2</sup>



**FLEXIBLE METAL HOSES**  
**S.S. CORRUGATED**  
**FLEXIBLE HOSES**  
Stainless steel  
AISI 304, AISI 321 and AISI316L  
Temp. -270°C to +600°C  
EN ISO 10380



**CONVOLUTED PTFE**  
**SINGLE BRAIDED SS 304**  
**COLOUR**  
Outer cover - Silver,  
Inner layer - Transparent  
Temp. -60°C to +260°C  
STANDARDS  
SAE J517-100R14



**SMOOTH BORE PTFE SINGLE**  
**BRAIDED SS 303 /304**  
**COLOUR**  
Outer cover - Silver,  
Inner layer - Transparent  
Temp. -60°C to +260°C  
STANDARDS  
SAE J517-100R14



**SMOOTH BORE PTFE DOUBLE**  
**BRAIDED SS 303 /304**  
**COLOUR**  
Outer cover - Silver,  
Inner layer - Transparent  
Temp. -60°C to +260°C  
STANDARDS  
SAE J517-100R14

**Pooja Shah - Sales**  
+91-99784 42215 | +91-70690 96458  
**Chirag Shah - Technical**  
+91-79903 36570  
**S.D. Shah - Director**  
+91-90990 16044

flexaflexhoses@gmail.com  
 www.flexaflexhoses.com  
www.hosesmarket.com

**FLEXAFLEX HOSES INTERNATIONAL**  
106, First Floor, Kailashpathi Chamber,  
Nr. Sunrise Restaurant, Reid Road,  
O/S Panchkuva Gate, Ahmedabad - 380 002