

# AIR DRILL BLACK HOSE



## Structure:

Inner Tube - Specially compounded natural Rubber.

Reinforcement - Single braid of high tensile Steel wire.

Cover :

Option 1: Specially compounded highly abrasion resistant natural rubber, black.







Option 2: Highly abrasion resistant modified Nitrile rubber - yellow. All sizes with perforated cover. Yellow cover MSHA IC11C. Flame Resistant.

## Applications:



Heavy duty, high pressure use on industrial construction and pneumatic mining applications, requiring an extra heavy duty hose with an oil resistant tube and abrasion resistant cover.

## Temperature range:

-30°C to +82°C

					
int mm	out mm	W.P. Kg/cm <sup>2</sup>	B.P. Kg/cm <sup>2</sup>	mm	in. Hg
20	28.3	34.5	138	152	25
25	36.6	34.5	138	201	25
32	44.2	34.5	138	254	25
38	50.5	34.5	138	304	15
50	63.5	34.5	138	355	15
63	79.7	34.5	138	762	10
75	93.3	34.5	138	914	10

**Pooja Shah - Sales**  
 +91-99784 42215 | +91-70690 96458  
**Chirag Shah - Technical**  
 +91-79903 36570  
**S.D. Shah - Director**  
 +91-90990 16044

 flexaflexhoses@gmail.com  
 www.flexaflexhoses.com  
 www.hosesmarket.com

**FLEXAFLEX HOSES INTERNATIONAL**  
 106, First Floor, Kailashpathi Chamber,  
 Nr. Sunrise Restaurant, Reid Road,  
 O/S Panchkuva Gate, Ahmedabad - 380 002