

AIR AND WATER HOSE



Structure:

Inner Tube - Modified Nitrile Rubber

Reinforcement - Single braid of High tensile synthetic yarn.

Outer Cover - Abrasion resistant Nitrile / Natural Rubber

Applications:







Air and Water applications in industries, Shipyards, Engineering work shops, Estates, Construction work, foundries, garages, steel mills etc.

Temperature range:

-30°C to +82°C




Standards

Exceeds I.S. 446 Type - I
I.S. 444 Type - II



					
int mm	out mm	W.P Kg/cm ²	B.P. Kg/cm ²	mm	in.Hg
12.50	20.0	12.0	36.0	127.0	30.0
20.00	28.5	12.0	36.0	152.0	25.0
25.00	35.5	12.0	36.0	203.0	15.0
31.50	43.5	12.0	36.0	254.0	10.0
38.00	50.0	12.0	36.0	304.0	8.0
50.00	65.0	12.0	36.0	419.1	4.0

Dunlop - Air & Water Hose



		
int mm	out mm	W.P Kg/cm ²
12.5	21	12
19	30	12
25	37	12
32	44	12
38	50	12
50	61	12
63	76	10
75	91	10
100	115	10

Pooja Shah - Sales
+91-99784 42215 | +91-70690 96458
Chirag Shah - Technical
+91-79903 36570
S.D. Shah - Director
+91-90990 16044

 flexaflexhoses@gmail.com
 www.flexaflexhoses.com
www.hosesmarket.com

FLEXAFLEX HOSES INTERNATIONAL
106, First Floor, Kailashpathi Chamber,
Nr. Sunrise Restaurant, Reid Road,
O/S Panchkuva Gate, Ahmedabad - 380 002