

EPDM CHEMICAL HOSE

flexAflex



Structure:






- Inner Tube - EPDM Rubber white and Black
- Reinforcement - Braided high tensile yarn
- Cover - Perforated synthetic rubber cover - EPDM - black

Applications:



For conveyance of a wide range of chemicals such as acids, alkalies, inorganic in salt and alcoholic materials.

Temperature range:

-30°C to +100°C

|  |  |  |  |  |
|---|---|--|---|---|
| int mm | out mm | W.P. bar | B.P. bar | mm |
| 19.0 | 31 | 12 | 48 | 152.0 |
| 25.0 | 38 | 12 | 48 | 203.0 |
| 31.0 | 45 | 12 | 48 | 215.0 |
| 38.0 | 52 | 12 | 48 | 254.0 |
| 50.0 | 68 | 12 | 48 | 355.0 |

Pooja Shah - Sales
+91-99784 42215 | +91-70690 96458
Chirag Shah - Technical
+91-79903 36570
S.D. Shah - Director
+91-90990 16044

 flexaflexhoses@gmail.com
 www.flexaflexhoses.com
www.hosesmarket.com

FLEXAFLEX HOSES INTERNATIONAL
106, First Floor, Kailashpathi Chamber,
Nr. Sunrise Restaurant, Reid Road,
O/S Panchkuva Gate, Ahmedabad - 380 002