

HEAVY ROCK DRILL HOSE



Structure:

Inner Tube - Modified Nitrile Rubber

Reinforcement - Single braid of high tensile synthetic yarn.

Cover - Abrasion, weather and heat resistant Nitrile / modified natural rubber

Applications:




Opencast mines, quarries, heavy duty pneumatic applications in industries, Road, building, tunnel construction.

Temperature range:

-30°C to +82°C





Standards

Exceeds I.S. 446 : 1987 Type -III



		
int mm	out mm	W.P Kg/cm ²
20	30	16
25	35.8	16
32	44	16
38	52	16
50	64	16
63	76	16
75	88	16

Indo - Maksson Rock Drill Hose



			
int mm	out mm	W.P. bar	B.P. bar
31	44.5	25	75
38	52	25	75
50	68	25	75
63	80.5	25	75
75	94	25	75
100	119.5	25	75

Pooja Shah - Sales
 +91-99784 42215 | +91-70690 96458
Chirag Shah - Technical
 +91-79903 36570
S.D. Shah - Director
 +91-90990 16044

 flexaflexhoses@gmail.com
 www.flexaflexhoses.com
 www.hosesmarket.com

FLEXAFLEX HOSES INTERNATIONAL
 106, First Floor, Kailashpathi Chamber,
 Nr. Sunrise Restaurant, Reid Road,
 O/S Panchkuva Gate, Ahmedabad - 380 002