

# LONGWALL MINE HOSE



## Structure:

- Inner Tube - Oil resistant Nitrile Rubber
- Reinforcement - Two braids of high tensile steel wire
- Cover - Modified Nitrile black or yellow. Self - extinguishing to meet MSHA requirements.







Available in Black & Yellow Cover

## Applications:



As flexible connections in high pressure water distribution and emulsion systems used in a variety of industries. The thick cover meets MSHA's self- extinguishing requirements, and is designed for the rough mining environment.

## Temperature range:

-40°C to +100°C

					
int mm	out mm	W.P. Kg/cm <sup>2</sup>	B.P. Kg/cm <sup>2</sup>	mm	bar
63.5	84.8	69	276	508.0	10.0
76.2	99.3	69	276	508.0	10.0

**Pooja Shah - Sales**  
+91-99784 42215 | +91-70690 96458  
**Chirag Shah - Technical**  
+91-79903 36570  
**S.D. Shah - Director**  
+91-90990 16044

 flexaflexhoses@gmail.com  
 www.flexaflexhoses.com  
www.hosesmarket.com

**FLEXAFLEX HOSES INTERNATIONAL**  
106, First Floor, Kailashpathi Chamber,  
Nr. Sunrise Restaurant, Reid Road,  
O/S Panchkuva Gate, Ahmedabad - 380 002