

# ROCK DRILL HOSE



## Structure:

Inner Tube - Modified Nitrile Rubber

Reinforcement - Single braid of high tensile synthetic yarn.

Cover - Abrasion, weather and heat resistant Nitrile / modified natural rubber

## Applications:

Opencast mines, quarries, heavy duty pneumatic applications in industries, Road, building, tunnel construction.

## Temperature range:

-30°C to +82°C

## Standards

Exceeds I.S. 446 Type -III

### Dunlop Rock Drill Hose



int mm	out mm	W.P Kg/cm²
12.0	23.0	18.0
20.0	30.0	16.0
25.0	37.0	16.0

### Indo - Maksson Rock Drill Hose



int mm	out mm	W.P. bar	B.P. bar	mm
6.0	15.0	14	56	76
8.0	16.0	14	56	102
10.0	18.0	14	56	102
12.5	22.0	14	56	127
19.0	29.5	14	56	152
25.4	37.0	14	56	203
31.0	43.5	14	56	254
38.0	51.5	14	56	305
50.0	65.0	14	56	305

int mm	out mm	W.P Kg/cm²	B.P. Kg/cm²	mm	in.Hg
12.5	19.8	21.0	84.0	127.0	25.0
20.0	28.0	21.0	84.0	152.0	25.0
25.0	37.8	21.0	84.0	203.0	25.0

**Pooja Shah - Sales**  
 +91-99784 42215 | +91-70690 96458  
**Chirag Shah - Technical**  
 +91-79903 36570  
**S.D. Shah - Director**  
 +91-90990 16044

flexaflexhoses@gmail.com  
 www.flexaflexhoses.com  
 www.hosesmarket.com

**FLEXAFLEX HOSES INTERNATIONAL**  
 106, First Floor, Kailashpathi Chamber,  
 Nr. Sunrise Restaurant, Reid Road,  
 O/S Panchkuva Gate, Ahmedabad - 380 002