

STATIC CONDUCTIVE HOSE

flexAflex

Temp. -40°C to +100°C



Structure:

- Inner Tube - NBR (Nitrile)
- Reinforcement - One or two braid of high tensile synthetic yarn.
- Cover
 - Specially compounded highly abrasion resistant nitrile rubber for size 12.5 & 20.0 mm. Black
 - Highly abrasion resistant modified natural Rubber for size 25.0 mm. Black

Applications:



industrial applications like Oil, Alcohol, Aqueous solution, Hydraulic Fluid, Acids, Detergent and Chemical. Static conductive hose.

Temperature range:

-40°C to +100°C

					
int mm	out mm	W.P. Kg/cm ²	B.P. Kg/cm ²	mm	in. Hg
6.3	12.7	37	110	35	760.0
8.0	15.0	37	110	50	760.0
10.0	17.0	37	110	60	760.0
12.5	20.5	37	110	70	635.0
16.0	24.2	30	90	90	500.0
19.0	29.0	30	90	110	500.0
25.0	35.0	30	90	130	500.0
31.5	42.8	30	90	200	250.0
38.0	51.0	30	90	300	250.0
50.0	64.0	30	90	500	250.0

Pooja Shah - Sales
+91-99784 42215 | +91-70690 96458
Chirag Shah - Technical
+91-79903 36570
S.D. Shah - Director
+91-90990 16044

 flexaflexhoses@gmail.com
 www.flexaflexhoses.com
www.hosesmarket.com

FLEXAFLEX HOSES INTERNATIONAL
106, First Floor, Kailashpathi Chamber,
Nr. Sunrise Restaurant, Reid Road,
O/S Panchkuva Gate, Ahmedabad - 380 002