

# SUPER STEAM HOSE DOUBLE WIRE BRAIDED

**Temp. -40°C to +232°C**



## Structure:

- Inner Tube - EPDM Black
- Reinforcement - Single braid of high tensile brass coated steel wire for size 12.7 mm.
  - Two braids of high tensile brass coated steel wire for size 20.0mm to 50.0 mm.
- Cover - EPDM Black. Perforated

## Applications:







Heavy duty industrial uses including heat control, melting of substances such as wax and glue, thawing, cleaning and steam transfer applications. It will handle all type of steam - saturated and superheated - up to 185 psi and + 232°C. Kindly avoid alternate change between steam and water

## Temperature range:



-40°C to +232°C

## Standards

Exceeds IS : 10655 Type 3 & B.S. : 5342 Type 2

					
int mm	out mm	W.P. Kg/cm <sup>2</sup>	B.P. Kg/cm <sup>2</sup>	mm	in. Hg
12.5	26.9	17.0	170.0	50.8	25.0
20.0	32.3	17.0	170.0	228.6	20.0
25.0	38.5	17.0	170.0	279.4	20.0
31.5	46.0	17.0	170.0	406.4	20.0
38.0	54.3	17.0	170.0	508.0	10.0
50.0	67.5	17.0	170.0	635.0	10.0

**Pooja Shah - Sales**  
+91-99784 42215 | +91-70690 96458  
**Chirag Shah - Technical**  
+91-79903 36570  
**S.D. Shah - Director**  
+91-90990 16044

 flexaflexhoses@gmail.com  
 www.flexaflexhoses.com  
www.hosesmarket.com

**FLEXAFLEX HOSES INTERNATIONAL**  
106, First Floor, Kailashpathi Chamber,  
Nr. Sunrise Restaurant, Reid Road,  
O/S Panchkuva Gate, Ahmedabad - 380 002