

STEAM HOSE SINGLE WIRE



Temp: -40°C to +195°C



Structure:

- Inner Tube - EPDM Rubber Black
- Reinforcement - Single braid of high tensile brass coated steel wire.
- Cover - EPDM Rubber Black Perforated

Applications:







For handling saturated and superheated up to 150 PSI and 195°C.
Not to be used alternatively for water and steam

Temperature range:



-40°C to +195°C

Standards

Exceeds IS : 10655 Type 2 & B.S. : 5342 Type 1

					
int mm	out mm	W.P. Kg/cm ²	B.P. Kg/cm ²	mm	in. Hg
20.0	28.3	10	100	254	25
25.0	36.6	10	100	304	15
31.5	44.2	10	100	406	15
38.0	50.5	10	100	508	15
50.0	63.5	10	100	635	15

Pooja Shah - Sales
+91-99784 42215 | +91-70690 96458
Chirag Shah - Technical
+91-79903 36570
S.D. Shah - Director
+91-90990 16044

 flexaflexhoses@gmail.com
 www.flexaflexhoses.com
www.hosesmarket.com

FLEXAFLEX HOSES INTERNATIONAL
106, First Floor, Kailashpathi Chamber,
Nr. Sunrise Restaurant, Reid Road,
O/S Panchkuva Gate, Ahmedabad - 380 002