



FLEXAFLEX HOSES INTERNATIONAL
Ahmedabad



Pooja Shah - Sales
+91-99784 42215 | +91-70690 96458



Chirag Shah - Technical
+91-79903 36570



S.D. Shah - Director
+91-90990 16044

J 7-9 PAINT-TWIN TUBE



Properties:

- ★Crush-proof
- ★Excellent resistance against solvents
- ★Best for the pressurized solvent transport

Structure:

The air hose and the pressurized solvent transport hose are paired

Material:

Inner: Nylon
Outer: polyurethane
Air hose material: PU
Air hose reinforcement: ester-polyurethane

Temperature range:

-5°C approx. to +70°C approx.

Applications:

- ★**pressurized paint & thinner transport**
- ★**pressurized paint transport tank & pump**

ID. Air mm	ID. Paint mm	OD. Air mm	OD. Paint mm	Working Pressure Kg/cm2	Std. Lengths meter
6.5	6.5	10	10	6	100
8	8	10	11	6 Air / 7 Paint	100



flexaflexhoses@gmail.com



www.flexaflexhoses.com
www.hosesmarket.com



FLEXAFLEX HOSES INTERNATIONAL
106, First Floor, Kailashpathi Chamber,
Nr. Sunrise Restaurant, Reid Road,
O/S Panchkuva Gate, Ahmedabad - 380 002